



THE COMPLETE FAÇADE SOLUTION
FIRE RATED SEALANT

FIRE RESISTANT SILICONE SEALANT FOR LINEAR SEALS IN WALLS AND FLOORS

Easy to use one component silicone the weather sealant for fireproof facades. It is also suitable in other industrial applications where good UV, thermal and fire resistance are required.

Features and Benefits

- Up to 4 hours fire resistance according to EN 1366-4
- Meeting relevant industry standards such as: ETA acc. EAD-350141-00-1106, EN 1366-4, EN 13501-2, BS 476-20, UL EU, UL 2079, Certifire, EN 10140-2, EN 15651-1, -4, ISO 11600 F 25 LM, ASTM C 920 class 25
- Excellent UV resistance
- Movement capability of $\pm 35\%$ (ASTM C 719)
- Easy to smooth and very good workability
- Good adhesion to many different substrates
- Neutral curing



Sikasil®-670 Fire

Designed for fire rated movement and connection joints on porous and non-porous substrates



What can Sika UK offer?

- Local supply
- Technical support
- Independently tested
- Readily Available
- Colours Available in black and grey

MORE INFORMATION

Contact: Andrew Hills | Mobile: : 07970 122265

Email: hills.andrew@uk.sika.com

www.sika.co.uk/facades

Connect with Andrew on LinkedIn:

<https://www.linkedin.com/in/andrew-hills-b83b073b/?originalSubdomain=uk>

Our most current General Sales Conditions shall apply.

Please consult the most current local Product Data Sheet prior to any use..



SIKA LIMITED

Head Office
Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
United Kingdom

Contact

Phone +44 1 707 394444
Fax +44 1 707 329129
E-Mail enquiries@uk.sika.com
www.sika.co.uk
@SikaLimited

BUILDING TRUST

